

Package ‘wordvector’

December 9, 2025

Type Package

Title Word and Document Vector Models

Version 0.6.0

Maintainer Kohei Watanabe <watanabe.kohei@gmail.com>

Description Create dense vector representation of words and documents using 'quanteda'. Currently implements Word2vec (Mikolov et al., 2013) <[doi:10.48550/arXiv.1310.4546](https://doi.org/10.48550/arXiv.1310.4546)> and Latent Semantic Analysis (Deerwester et al., 1990) <[doi:10.1002/\(SICI\)1097-4571\(199009\)41:6%3C391::AID-ASII%3E3.0.CO;2-9](https://doi.org/10.1002/(SICI)1097-4571(199009)41:6%3C391::AID-ASII%3E3.0.CO;2-9)>.

URL <https://github.com/koheiw/wordvector>

License Apache License (>= 2.0)

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 3.5.0)

Imports quanteda (>= 4.1.0), methods, stringi, Matrix, proxyC, RSpectra, irlba, rsvd

Suggests testthat, word2vec, spelling

LinkingTo Rcpp, quanteda

Language en-US

LazyData true

NeedsCompilation yes

Author Kohei Watanabe [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0001-6519-5265>>),
Jan Wijffels [aut] (Original R code),
BNOSAC [cph] (Original R code),
Max Fomichev [ctb, cph] (Original C++ code)

Repository CRAN

Date/Publication 2025-12-09 09:50:02 UTC

Contents

analogy	2
as.matrix.textmodel_doc2vec	3
as.textmodel_doc2vec	3
data_corpus_news2014	4
probability	5
similarity	5
textmodel_doc2vec	6
textmodel_lsa	8
textmodel_word2vec	9
Index	12

analogy	<i>Convert formula to named character vector</i>
---------	--

Description

Convert a formula to a named character vector in analogy tasks.

Usage

```
analogy(formula)
```

Arguments

formula a [formula](#) object that defines the relationship between words using + or - operators.

Value

a named character vector to be passed to [similarity\(\)](#).

See Also

```
similarity\(\)
```

Examples

```
analogy(~ berlin - germany + france)
analogy(~ quick - quickly + slowly)
```

```
as.matrix.textmodel_doc2vec
```

Extract word or document vectors

Description

Extract word or document vectors from a textmodel_word2vec or textmodel_doc2vec object.

Usage

```
## S3 method for class 'textmodel_doc2vec'
as.matrix(x, normalize = TRUE, layer = c("documents", "words"), ...)

## S3 method for class 'textmodel_word2vec'
as.matrix(x, normalize = TRUE, layer = "words", ...)
```

Arguments

x	a textmodel_word2vec or textmodel_doc2vec object.
normalize	if TRUE, returns normalized vectors.
layer	the layer from which the vectors are extracted.
...	not used.

Value

a matrix that contain the word or document vectors in rows.

```
as.textmodel_doc2vec
```

Create distributed representation of documents

Description

Create distributed representation of documents as weighted word vectors.

Usage

```
as.textmodel_doc2vec(
  x,
  model,
  normalize = FALSE,
  weights = 1,
  pattern = NULL,
  group_data = FALSE,
  ...
)
```

Arguments

x	a quanteda::tokens or quanteda::dfm object.
model	a <code>textmodel_wordvector</code> object.
normalize	if TRUE, normalized word vectors before creating document vectors.
weights	weight the word vectors by user-provided values; either a single value or multiple values sorted in the same order as the word vectors.
pattern	quanteda::pattern to select words to apply weights.
group_data	if TRUE, apply <code>dfm_group(x)</code> before creating document vectors.
...	additional arguments passed to quanteda::object2id .

Value

Returns a `textmodel_docvector` object with the following elements:

values	a list of matrices for word and document vectors.
dim	the size of the document vectors.
concatenator	the concatenator in x.
docvars	document variables copied from x.
normalize	if the document vectors are normalized.
call	the command used to execute the function.
version	the version of the wordvector package.

data_corpus_news2014 *Yahoo News summaries from 2014*

Description

A corpus object containing 2,000 news summaries collected from Yahoo News via RSS feeds in 2014. The title and description of the summaries are concatenated.

Usage

```
data_corpus_news2014
```

Format

An object of class `corpus` (inherits from `character`) of length 20000.

Source

<https://www.yahoo.com/news/>

References

Watanabe, K. (2018). Newsmap: A semi-supervised approach to geographical news classification. *Digital Journalism*, 6(3), 294–309. <https://doi.org/10.1080/21670811.2017.1293487>

probability	<i>Compute probability of words</i>
-------------	-------------------------------------

Description

Compute the probability of words given other words.

Usage

```
probability(  
  x,  
  targets,  
  layer = c("words", "documents"),  
  mode = c("character", "numeric")  
)
```

Arguments

x	a trained textmodel_wordvector object.
targets	words for which probabilities are computed.
layer	the layer based on which probabilities are computed.
mode	specify the type of resulting object.

Value

a matrix of words or documents sorted in descending order by the probability scores when mode = "character"; a matrix of the probability scores when mode = "numeric". When words is a named numeric vector, probability scores are weighted by the values.

See Also

[similarity\(\)](#)

similarity	<i>Compute similarity between word or document vectors</i>
------------	--

Description

Compute the cosine similarity between word vectors for selected words.

Usage

```
similarity(
  x,
  targets,
  layer = c("words", "documents"),
  mode = c("character", "numeric")
)
```

Arguments

<code>x</code>	a <code>textmodel_wordvector</code> object.
<code>targets</code>	words or documents for which similarity is computed.
<code>layer</code>	the layer based on which similarity is computed. This must be "documents" when targets are document names.
<code>mode</code>	specify the type of resulting object.

Value

a matrix of cosine similarity scores when `mode = "numeric"` or of words sorted in descending order by the similarity scores when `mode = "character"`. When words is a named numeric vector, word (or document) vectors are weighted and summed before computing similarity scores.

See Also

[probability\(\)](#)

<code>textmodel_doc2vec</code>	<i>Doc2vec model</i>
--------------------------------	----------------------

Description

Train a doc2vec model (Le & Mikolov, 2014) using a [quanteda::tokens](#) object.

Usage

```
textmodel_doc2vec(
  x,
  dim = 50,
  type = c("dm", "dbow"),
  min_count = 5,
  window = 5,
  iter = 10,
  alpha = 0.05,
  model = NULL,
  use_ns = TRUE,
  ns_size = 5,
```

```

    sample = 0.001,
    tolower = TRUE,
    include_data = FALSE,
    verbose = FALSE,
    ...
)

```

Arguments

x	a quanteda::tokens or quanteda::tokens_xptr object.
dim	the size of the word vectors.
type	the architecture of the model; either "dm" (distributed memory) or "dbow" (distributed bag-of-words).
min_count	the minimum frequency of the words. Words less frequent than this in x are removed before training.
window	the size of the window for context words. Ignored when type = "dbow" as its context window is the entire document (sentence or paragraph).
iter	the number of iterations in model training.
alpha	the initial learning rate.
model	a trained Word2vec model; if provided, its word vectors are updated for x.
use_ns	if TRUE, negative sampling is used. Otherwise, hierarchical softmax is used.
ns_size	the size of negative samples. Only used when use_ns = TRUE.
sample	the rate of sampling of words based on their frequency. Sampling is disabled when sample = 1.0
tolower	lower-case all the tokens before fitting the model.
include_data	if TRUE, the resulting object includes the data supplied as x.
verbose	if TRUE, print the progress of training.
...	additional arguments.

Value

Returns a `textmodel_doc2vec` object with matrices for word and document vector values in `values`. Other elements are the same as [textmodel_word2vec](#).

References

Le, Q. V., & Mikolov, T. (2014). Distributed Representations of Sentences and Documents (No. arXiv:1405.4053). arXiv. <https://doi.org/10.48550/arXiv.1405.4053>

textmodel_lsa

Latent Semantic Analysis model

Description

Train a Latent Semantic Analysis model (Deerwester et al., 1990) on a [quanteda::tokens](#) object.

Usage

```
textmodel_lsa(
  x,
  dim = 50,
  min_count = 5L,
  engine = c("RSpectra", "irlba", "rsvd"),
  weight = "count",
  tolower = TRUE,
  verbose = FALSE,
  ...
)
```

Arguments

x	a quanteda::tokens or quanteda::tokens_xptr object.
dim	the size of the word vectors.
min_count	the minimum frequency of the words. Words less frequent than this in x are removed before training.
engine	select the engine perform SVD to generate word vectors.
weight	weighting scheme passed to quanteda::dfm_weight() .
tolower	if TRUE lower-case all the tokens before fitting the model.
verbose	if TRUE, print the progress of training.
...	additional arguments.

Value

Returns a textmodel_wordvector object with the following elements:

values	a matrix for word vectors values.
weights	a matrix for word vectors weights.
frequency	the frequency of words in x.
engine	the SVD engine used.
weight	weighting scheme.
min_count	the value of min_count.
concatenator	the concatenator in x.
call	the command used to execute the function.
version	the version of the wordvector package.

References

Deerwester, S. C., Dumais, S. T., Landauer, T. K., Furnas, G. W., & Harshman, R. A. (1990). Indexing by latent semantic analysis. *JASIS*, 41(6), 391–407.

Examples

```
library(quanteda)
library(wordvector)

# pre-processing
corp <- corpus_reshape(data_corpus_news2014)
toks <- tokens(corp, remove_punct = TRUE, remove_symbols = TRUE) %>%
  tokens_remove(stopwords("en", "marimo"), padding = TRUE) %>%
  tokens_select("[a-zA-Z-]+$", valuetype = "regex", case_insensitive = FALSE,
    padding = TRUE) %>%
  tokens_tolower()

# train LSA
lsa <- textmodel_lsa(toks, dim = 50, min_count = 5, verbose = TRUE)

# find similar words
head(similarity(lsa, c("berlin", "germany", "france"), mode = "words"))
head(similarity(lsa, c("berlin" = 1, "germany" = -1, "france" = 1), mode = "values"))
head(similarity(lsa, analogy(~ berlin - germany + france)))
```

textmodel_word2vec	<i>Word2vec model</i>
--------------------	-----------------------

Description

Train a word2vec model (Mikolov et al., 2013) using a [quanteda::tokens](#) object.

Usage

```
textmodel_word2vec(
  x,
  dim = 50,
  type = c("cbow", "sg", "dm"),
  min_count = 5,
  window = ifelse(type == "sg", 10, 5),
  iter = 10,
  alpha = 0.05,
  model = NULL,
  use_ns = TRUE,
  ns_size = 5,
  sample = 0.001,
  tolower = TRUE,
```

```

    include_data = FALSE,
    verbose = FALSE,
    ...
)

```

Arguments

x	a quanteda::tokens or quanteda::tokens_xptr object.
dim	the size of the word vectors.
type	the architecture of the model; either "cbow" (continuous back-of-words), "sg" (skip-gram), or "dm" (distributed memory).
min_count	the minimum frequency of the words. Words less frequent than this in x are removed before training.
window	the size of the word window. Words within this window are considered to be the context of a target word.
iter	the number of iterations in model training.
alpha	the initial learning rate.
model	a trained Word2vec model; if provided, its word vectors are updated for x.
use_ns	if TRUE, negative sampling is used. Otherwise, hierarchical softmax is used.
ns_size	the size of negative samples. Only used when use_ns = TRUE.
sample	the rate of sampling of words based on their frequency. Sampling is disabled when sample = 1.0
tolower	lower-case all the tokens before fitting the model.
include_data	if TRUE, the resulting object includes the data supplied as x.
verbose	if TRUE, print the progress of training.
...	additional arguments.

Details

If type = "dm", it trains a doc2vec model but saves only word vectors to save storage space. [textmodel_doc2vec](#) should be used to access document vectors.

Users can changed the number of processors used for the parallel computing via `options(wordvector_threads)`.

Value

Returns a `textmodel_word2vec` object with the following elements:

values	a list of a matrix for word vector values.
weights	a matrix for word vector weights.
dim	the size of the word vectors.
type	the architecture of the model.
frequency	the frequency of words in x.
window	the size of the word window.

iter	the number of iterations in model training.
alpha	the initial learning rate.
use_ns	the use of negative sampling.
ns_size	the size of negative samples.
min_count	the value of min_count.
concatenator	the concatenator in x.
data	the original data supplied as x if include_data = TRUE.
call	the command used to execute the function.
version	the version of the wordvector package.

References

Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013). Distributed Representations of Words and Phrases and their Compositionality. <https://arxiv.org/abs/1310.4546>.

Examples

```
library(quantda)
library(wordvector)

# pre-processing
corp <- data_corpus_news2014
toks <- tokens(corp, remove_punct = TRUE, remove_symbols = TRUE) %>%
  tokens_remove(stopwords("en", "marimo"), padding = TRUE) %>%
  tokens_select("^[a-zA-Z-]+$", valuetype = "regex", case_insensitive = FALSE,
    padding = TRUE) %>%
  tokens_tolower()

# train word2vec
wov <- textmodel_word2vec(toks, dim = 50, type = "cbow", min_count = 5, sample = 0.001)

# find similar words
head(similarity(wov, c("berlin", "germany", "france"), mode = "words"))
head(similarity(wov, c("berlin" = 1, "germany" = -1, "france" = 1), mode = "values"))
head(similarity(wov, analogy(~ berlin - germany + france), mode = "words"))
```

Index

* datasets

data_corpus_news2014, [4](#)

analogy, [2](#)

as.matrix.textmodel_doc2vec, [3](#)

as.matrix.textmodel_word2vec
(as.matrix.textmodel_doc2vec),
[3](#)

as.textmodel_doc2vec, [3](#)

data_corpus_news2014, [4](#)

formula, [2](#)

probability, [5](#)

probability(), [6](#)

quanteda::dfm, [4](#)

quanteda::dfm_weight(), [8](#)

quanteda::object2id, [4](#)

quanteda::pattern, [4](#)

quanteda::tokens, [4](#), [6–10](#)

quanteda::tokens_xptr, [7](#), [8](#), [10](#)

similarity, [5](#)

similarity(), [2](#), [5](#)

textmodel_doc2vec, [6](#), [10](#)

textmodel_lsa, [8](#)

textmodel_word2vec, [7](#), [9](#)